

**Environex**  
International



# Synergy

15 YEAR WARRANTY

CSIRO TESTED

Consolidator/Penetrating Sealer



**SYNERGY** is a world class combination consolidator and penetrating sealer specially formulated for superior stain and salt protection around swimming pools. **SYNERGY** is suitable for internal, external, domestic and commercial surfaces and will prevent permanent staining from most common spills.

To minimize the effects of salt attack **ENVIRONEX** recommends installing a 40mm overflow pipe located approximately 150mm beneath the pool coping. This will remove the chance of the coping being regularly submersed in the corrosive pool water environment.

- Do not seal under 10°C or over 30°C.
- Always wear Personal Protective Equipment (PPE) – A minimum requirement of Safety Glasses, Gloves, Mask & Boots.
- Apply a minimum of 2 coats of **SYNERGY** to a clean dry surface with an **ENVIRONEX LAMBSWOOL APPLICATOR** or **ENVIRONEX VITON SEAL SPRAYER**. **SYNERGY** may take 2 to 3 days to dry. **ENVIRONEX** recommend dip sealing your coping pavers/tiles with **SYNERGY**. Porous masonry will require more coats (3-5) of **SYNERGY** to provide adequate protection. Allow minimum 7 days curing.
- Only use **REFRESH** pH neutral detergent for daily or weekly maintenance.
- Not suitable for Bluestone.
- **ENVIRONEX** recommend resealing the pool surrounds every 2-3 years to assist in prevention of Salt Attack.
- Always test first.



Technical Assistance 1800 999 196  
[www.environex.net.au](http://www.environex.net.au)

*The Next Generation in Specialty Formulators*

